

- |  |   |
|--|---|
| <ul style="list-style-type: none"> <li>• Accuracy Class</li> <li>• Maximum Rated Current</li> <li>• Nominal Voltage</li> </ul>   | <p>1<br/>100A<br/>1 Phase – 230V AC<br/>3 Phase – 230/400V AC (3-)<br/>0.25A – 100A<br/>1000A for 0.01s<br/>50-60Hz<br/>1000 impulses per kWh<br/>Mains Power On<br/>Flashing on Load<br/>Backlit Blue LCD<br/>1 Phase: 25mm<sup>2</sup> (Neutral 2.5mm<sup>2</sup>)<br/>3 Phase: 25mm<sup>2</sup> (Neutral 4mm<sup>2</sup>)<br/>-20°C to 55°C<br/>IEC62052-11, IEC62053-21<br/>1 year<br/>3.6V Lithium<br/>Fire Resistant ABS<br/>IP51<br/>Kit Available</p> |
| <ul style="list-style-type: none"> <li>• Operational Current Range</li> <li>• Over Current Withstand</li> <li>• Operational Frequency Range</li> <li>• Test Output Flash Rate</li> <li>• Power Supply Indicator</li> <li>• Consumption Indicator</li> <li>• Display</li> <li>• Maximum Cable Capacity</li> </ul> |   |
| <ul style="list-style-type: none"> <li>• Operating Temperature</li> <li>• International Standard</li> <li>• Warranty</li> <li>• Backup Battery</li> <li>• Housing Material</li> <li>• Weatherproof Rating</li> <li>• Tamper Proof</li> </ul>   |   |

**DIMENSIONS:**

**1 PHASE**

90mm (H) x 18mm (W) x 72mm (D) 1 Module  
New Slimline Design

**3 PHASE**

100mm (H) x 122mm (W) x 65mm (D) 7 Module



FKW - 15110



FKW - 15120

Code	Description	Packing	MOQ	Ctn
FKW - 15110	DIN mount Direct Electronic 0-100A - Single Phase	1	1	20
FKW - 15120	DIN mount Direct Electronic 0-100A - Three Phase	1	1	5