



Technical Specifications:

Light Colour:	Warm White [3000K] Natural Light [Daylight 4000K] Cool White [6000K]
Power:	13W
Input Voltage:	220-240V AC 50/60Hz
Driver:	Dimmable [Trailing Edge]
Class:	IC-4 IC-F [New Zealand]
Rated Lifespan:	50,000 Hours
Beam Angle:	90°
IP Rating:	IP44
Housing Material:	Aluminium
Thermal Insulation Clearance:	Side Abutted & Covered Permitted
Building Elements Clearance:	May abut the luminaire on the sides or the top [HCB & SCB = 0mm]
Flange colour:	Matt White / Brushed Chrome
Connection:	External Driver, Plug and Lead
Ceiling hole:	90-95mm
Dimensions:	35mm Height x 110mm Outer Diameter
Air Transfer Category:	Closed

Model:

Model	Colour	Lumens
LD13T90-WW-W LD13T90-WW-S	Warm White	950
LD13T90-NW-W LD13T90-NW-S	Natural White	1050
LD13T90-CW-W LD13T90-CW-S	Cool White	1100

Accessories

LDF140 & LDF140-S [adapter flange 110-130mm]
LDF170 & LDF170-S [adapter flange 110-160mm]

Compliance:

AS/NZS 60598.2.2. [incl. NZ Amendment A]
AS/NZS CISPR 15
IEC 61347.2.13

