

LD23T200-WW-W, LD23T200-NW-W, LD23T200-CW-W






Technical Specifications:


| Power: | 23W | |
|----------------------------------|--|--|
| Input Voltage: | 220-240V AC 50/60Hz | |
| Driver: | Dimmable (Trailing Edge) | |
| Class: | IC-4 IC-F (New Zealand) | |
| Light Source: | Epistar (tm) | |
| Rated Lifepspan: | 35,000 Hours | |
| Beam Angle: | 90° | |
| IP Rating: | IP20 | |
| Thermal Insulation Clearance: | Side Abutted & Covered | |
| Building Elements Clearance: | May abut the luminaire on the sides or the top (HCB & SCB = 0mm) | |
| Flange colour: | Matt White | |
| Connection: | External Driver, Plug and Lead (1m) | |
| Ceiling hole: | 200mm | |
| Dimensions: | 28mm Height x 230mm Outer Diameter | |
| Driver Height: | 28mm | |
| Air Transfer Category: | Closed | |
| | | |

Model:

| MODEL | COLOUR | LUMENS |
|---------------|---------------|--------|
| LD23T200-WW-W | Warm White | 2150 |
| LD23T200-NW-W | Natural White | 2250 |
| LD23T200-CW-W | Cool White | 2270 |

Dimensions:





Compliance:

AS/NZS60598.1.2003 AS/NZS60598.2.2:2001 Including Amendment A

