



Technical Specifications:

Material:	Oxygen Free High Conductivity Copper
Finish:	Electroplated Tin Fully Annealed
Temperature Range:	-55°C To +155°C
Entry:	Straight

Compliance:

AS/NZS 4325:1
EN 60998-1

Voltex Code	Cable mm2	Dimensions mm		
		Barrel ID	Barrel OD	Total Length
		A	C	J
CL-1.5	1.5	1.8	3.7	22
CL-2.5	2.5	2.4	4	22
CL-4	4	3.1	4.8	22
CL-6	6	3.8	5.5	22
CL-10	10	4.7	7.1	22
CL-16	16	5.5	7.9	44
CL-25	25	7.1	9.5	47
CL-35	35	8.2	11.2	47
CL-50	50	9.5	12.8	47
CL-70	70	11.2	14.3	50
CL-95	95	13.5	17.4	54
CL-120	120	15.6	20.6	65
CL-150	150	16.7	22.5	65
CL-185	185	18.4	24.2	65
CL-240	240	21.2	28.2	90
CL-300	300	23.5	31.3	90
CL-400	400	26.8	34.8	90
CL-500	500	30	39	112
CL-630	630	34	45	112
CL-800	800	39.3	53.3	230
CL-1000	1000	44	60	230

