



DL9T90-10MM



DL9T90-10MM-FB



DL9T90-10MM-FS

Technical Specifications:

Power	9W
Input Voltage [Driver]	220-240V AC 50 Class II
Driver [Independent type]	Dimmable [trailing edge], Class II, SELV, IC classification Dimensions: 100mm L x 42mm W x 21mm D
Class	IC-4 IC-F [New Zealand]
Light Source	LED CRI >80
Light Colour [Temperature]	Warm White [3000K] Natural White [4000K] Cool White [5000K]
Ambient Temperature	ta 25°C
Lumen Output	550-650 Lumens
Beam Angle	110°
Rated Lifespan	50,000 Hours
IP rating	Driver: IP20 Luminaire: IP44 [Light face]; IP4X [Rear enclosure]
Building Element and Thermal Insulation Clearance	May abut the luminaire on the sides or cover the rear enclosure [MCI & SCI = 0mm] [HCB & SCB = 0mm]
Minimum distance from lighted objects	0.1m
Ceiling Hole	90-95mm
Dimensions	10mm Height* x 115mm [Outer Diameter]
Air Transfer Category:	Closed

Accessories:

DL9T90-10MM-FB
DL9T90-10MM-FS
[Silver and Black cover rings]

Compliance:

AS/NZS 60598.2.2. [incl. NZ Amendment A]
AS/NZS CISPR 15
IEC 61347.2.13

Dimensions:

