



EXLS

**TECHNICAL SPECIFICATIONS**

|                    |  |
|--------------------|--|
| Voltage            | 220-240V, 50Hz                           |
| Lumen Output       | 25lm                                     |
| Mains Power        | 3W Max                                   |
| Emergency Power    | 1W Max                                   |
| Battery            | LiFePO4 3.2V 600mAh                      |
| Charge Time        | ≥16H                                     |
| Discharge Duration | ≥2H                                      |
| CCT/CRI            | 6000K/Ra>80                              |
| Visibility         | 24M                                      |
| Test Mode          | AT / MT                                  |
| Life Span [Hours]  | 50,000                                   |
| Wiring             | Terminal Block [0.75-6mm <sup>2</sup> ]  |
| Protection Class   | Class II                                 |
| IP Rating          | IP20                                     |
| Compliance         | AS/NZS 2293.3                            |
| Warranty           | 7 Years on Fitting<br>3 Years on Battery |

**STRUCTURE**

|                     |   |
|---------------------|---|
| Material            | PC  |
| LGP                 | Acrylic [PMMA]                                  |
| Decal               | PVC   |
| EM Classification   | C0:D2.5, C90:D2.0                               |
| Operating Temp [°C] | 0°C~45°C  |
| Mounting            | Ceiling/Wall/Recessed<br>[Optional fitting kit] |

