



Technical Specifications:

Light colour [Temperature]	Warm White [3000K] Natural Light [Daylight 4000K] Cool White [6000K]
Lumens	Warm White [1645] Natural White [1769] Cool White [1702]
Power	18W
Input Voltage	220-240V AC 50/60Hz
Driver	Dimmable [Trailing Edge]
Class	IC-4 D IC-F [New Zealand]
Light Source	Epistar™
Rated Lifespan	35,000 Hours
Beam Angle	90°
IP Rating	IP20
Thermal Insulation Clearance	Side Abutted & Covered
Building Elements Clearance	May abut the luminaire on the sides or the top [HCB & SCB = 0mm]
Flange colour	Matte White
Connection	External Driver, Plug and Lead
Ceiling hole	160mm
Dimensions	27mm Height x 180mm Outer Diameter

Driver Height	27mm
Air Transfer Category	Closed
Accessories	IDLF140 [110-130mm adaptor flange] IDLF170 [110-160mm adaptor flange]

Compliance:

AS/NZS60598.1.2003
AS/NZS60598.2.2:2001 Including Amendment A

Model:

MODEL	COLOUR	LUMENS
LD18T160-WW-W	Warm White	1645
LD18T160-NW-W	Natural White	1769
LD18T160-CW-W	Cool White	1702

Dimensions:

