




Brushed Silver Frame



Black Frame



110-130mm Flange



110-160mm Flange

### Technical Specifications:

Light Colour:	3000K, 4000K, 6000K
Power:	9W
Input Voltage:	220-240V AC 50/60Hz
Driver:	Integrated - Dimmable (Trailing)
Class:	IC-4 IC-F (New Zealand)
Light Source:	San'an
Light Colour (Temperature) :	Warm White (3000K), Natural White (Daylight 4000K) or Cool White (6000K)
Lumen Output:	900-1000 Lumens
Rated Lifespan :	40,000 Hours
Beam Angle :	90°
IP Rating:	IP44
Thermal Insulation Clearance:	May abut the luminaire on the sides or cover the top (MCI & SCI = 0mm)
Building Elements Clearance:	May abut the luminaire on the sides or the top (HCB & SCB = 0mm)

Flange Colour :	White
Connection :	Integrated Driver, Supply Plug & 1.2m Flexible Cord
Ceiling Hole:	90-95mm
Dimensions :	60mm Height x 115mm Outer Diameter
Air Transfer Category:	Closed
Accessories::	IDL9T90-B IDL9T90-S (Silver and Black cover rings) IDLF140 IDLF170

### Compliance:

AS/NZS 60598.2.2. (incl. NZ Amendment A)  
AS/NZS CISPR 15  
IEC 61347.2.13

