



Brushed Silver Frame



Black Frame



110-130mm Flange



110-160mm Flange

Technical Specifications:

Light Colour	3000K, 4000K, 6000K
Power	9W
Input Voltage	220-240V AC 50/60Hz
Driver	Integrated - Dimmable [Trailing]
Class	IC-4 IC-F [New Zealand]
Light Source	San'an
Light Colour [Temperature]	Warm White [3000K], Natural White [Daylight 4000K] or Cool White [6000K]
Lumen Output	900-1000 Lumens
Rated Lifespan	40,000 Hours
Beam Angle	90°
CRI	>80
IP Rating	IP44
Thermal Insulation Clearance	May abut the luminaire on the sides or cover the top [MCI & SCI = 0mm]
Building Elements Clearance	May abut the luminaire on the sides or the top [HCB & SCB = 0mm]

Flange Colour	White
Connection	Integrated Driver, Supply Plug & 1.2m Flexible Cord
Ceiling Hole	90-95mm
Dimensions	60mm Height x 115mm Outer Diameter
Air Transfer Category	Closed
Accessories	IDL9T90-B IDL9T90-S [Silver and Black cover rings] IDLF140 IDLF170

Compliance:

AS/NZS 60598.2.2. [incl. NZ Amendment A]
AS/NZS CISPR 15
IEC 61347.2.13

