



Specifications:

| | |
|-------------------------------------|--|
| Cover Material: | Polycarbonate |
| Protection type: | Without protection [No RCD] |
| IP rating: | IP66 |
| Optimum Operating temperature: | -25 to +50C |
| UV Resistant: | Yes |
| Chemical resistant: | Low - Not suitable for environments with chemicals/ oils |
| Cable entry in enclosure: | 25mm x 2 and 32mm x 1 |
| Max Terminal size for cable: | 25mm ² |
| Appropriate entry reducers included | |

Compliance:

| |
|-------------|
| AS/NZS 3123 |
| AS/NZS 3121 |
| AS/NZS 3100 |

| Reference | Volts | Amp | Pin No | Socket Conf. |
|-----------|-------|-----|--------|--------------|
| C66SO320 | 250 | 32 | 3 | |
| C66SO332 | 250 | 32 | 3 | |
| C66SO410 | 500 | 10 | 4 | |
| C66SO420 | 500 | 20 | 4 | |
| C66SO432 | 500 | 32 | 4 | |
| C66SO440 | 500 | 40 | 4 | |
| C66SO450 | 500 | 50 | 4 | |
| C66SO510 | 500 | 10 | 5 | |
| C66SO520 | 500 | 20 | 5 | |
| C66SO532 | 500 | 32 | 5 | |
| C66SO540 | 500 | 40 | 5 | |
| C66SO550 | 500 | 50 | 5 | |

Dimensions:

