√OLTEX[®] PRODUCT DATA SHEET




- Daily, Weekly Sunset/Sunrise programming
- ON, OFF and pulse outputs
- Random switching function
- Manual override
- Automatic summertime update
- Backup Battery life: 5 years (replaceable)
- Low battery warning

Android/iOS App functions:

- Create time switching programs Transfer switching programs onto
- multiple devices Acquire programs from a device and
- copy them to other device Test relay outputs
- lescreiay outputs
 - Acquire settings (date, time, coordinates, etc) automatically and transfer them to the device

Wiring:




Specifications:


Power supply	240Vac 50Hz
Relay capacity	16A @ 240Vac
Loads	Incandescent 2000 W Fluorescent 250 VA Low voltage halogen 1000 VA Halogen (240 V) 2000 W CFL 200 VA LED 500 VA
Battery life/type	5 years/Lithium CR-2032
Programming resolution	1 minute
Programming	120 programmable events Daily, Weekly, Sunset/Sunrise programming
Resolution of programming	1 minute
Operating accuracy	± 1 second/day at 25°C
Operating temperature	-20 to +50°C
Storage temperature	-10 to +70 °C
Operating humidity	RH 20 to 90 % non-condensing
Housing	2 DIN modules
Protection degree	IP20
Quiescent Power	2W
Terminal size	1 x 4mm² cable maximum

Programming Options:

Time Programming



Astronomical Programming



Z YEAR WARRANTY

