

Technical Specifications:

Input Voltage:	200-260 VAC 50/60Hz
Opal diffuser material:	UV Stabilized Polycarbonate (PC) Opaque White
Body material:	Polycarbonate (PC) Grey
Fireproof grade:	V-0
Input Power [Watts]:	28W
Clips & Mounting Brackets:	304 Stainless Steel
Terminal Block:	3 Poles Screw Terminal 6mm ² capacity
Driver Efficiency:	>85.1
Driver:	OSRAM® OPTOTRONIC [Non Dimmable]
LED Brand:	LG®
LED Type:	SMD2835
LED Qty [Pcs]:	50
CCT - Colour Temperature [Kelvin]:	5000K
CRI [Colour Rendering Index]:	>80
Typical Lumens [+/-5%]:	2500Lm
Lighting Efficiency:	up to 105Lm/W
Power Factor:	>0.95
Beam Angle:	120°
IK rating [Input Resistance]:	IK08 [Protection against 5 joule impact]
IP rating:	IP66
Warranty:	7 years
Net Weight:	1.3kg
Product Size [mm]:	600 [L] x 120 [W] x 108 [H]
Fixing Hole Centre:	330mm
Maximum Luminaires per circuit [Typical] Type C 16A:	85
Operating temperature:	-20°C to +50°C



Compliance

ROHS,
 EN62471,
 ISO 9001:2008

