




WPP2H-LEDV2



WPP2HS-LEDV2



WPP2HB-LEDV2



WPP2HSB-LEDV2



TECHNICAL SPECIFICATIONS

Product Code	Mounting Block	IP Rating	Current Rating	Colour
WPP2HB-LEDV2	Standard	IP54	10A	Matte Black
WPP2H-LEDV2	Standard	IP54	10A	Grey RAL7047
WPP2HSB-LEDV2	Slim	IP54	10A	Matte Black
WPP2HS-LEDV2	Slim	IP54	10A	Grey RAL7047



TECHNICAL SPECIFICATIONS

Materials	Polycarbonate UV Stabilised
Description/ Technical Data	<p>Safety Shutters Terminal Dimensions: 6.0mm x 6.5mm = 39mm²</p> <p>Conduit entries: Standard mounting block (40mm deep): 5 x 25mm entries</p> <p>Slim mounting block (25mm deep): 1 x 25mm rear entry</p> <p>1 x Plain Reducer 25/20mm included in standard version</p>
LED Detail	<p>4K Natural White</p> <p>LED is 0.25W Maximum</p> <p>Ambient Light Sensing - LED will come on at low light levels, and will adjust brightness based on ambient light level (low brightness with some ambient light, ramping to full brightness with no ambient light)</p>
Installation	<p>All entries should be silicone sealed to maintain IP rating</p> <p>Pips must be fitted to maintain IP rating</p> <p>Install vertically with sockets facing down</p> <p>Cover screws: tighten to 0.8Nm recommended</p>
Compliance	AS/NZS3112: 2017 + A1 AS/NZS3100: 2022 + A1
Warranty	25 years, 7 years on LED Light

DIMENSIONS

