

VOLTEx®
PRODUCT DATA SHEET

Voltex Weatherproof Power Points

Grey and Matte Black



WPP2HV2



WPP2HSV2



WPP2HBV2



WPP1HV2



WPP2HXV2



WPP1HSBV2

TECHNICAL SPECIFICATIONS

Product Code	Mounting Block	IP Rating	Current Rating	Colour
WPP1H-15BV2	Standard	IP54	15A	Matte Black
WPP1H-15V2	Standard	IP54	15A	Grey RAL7047
WPP1HBV2	Standard	IP54	10A	Matte Black
WPP1HSBV2	Slim	IP54	10A	Matte Black
WPP1HSV2	Slim	IP54	10A	Grey RAL7047
WPP1HV2	Standard	IP54	10A	Grey RAL7047
WPP2H-15BV2	Standard	IP54	15A	Matte Black
WPP2H-15V2	Standard	IP54	15A	Grey RAL7047
WPP2HBV2	Standard	IP54	10A	Matte Black
WPP2HSBV2	Slim	IP54	10A	Matte Black
WPP2HSV2	Slim	IP54	10A	Grey RAL7047
WPP2HV2	Standard	IP54	10A	Grey RAL7047
WPP2HXBV2	Standard	IP54	10A Extra switch rated to 10A	Matte Black
WPP2HXV2	Standard	IP54	10A Extra switch rated to 10A	Grey RAL7047

TECHNICAL SPECIFICATIONS

Materials	Polycarbonate UV Stabilised
Description/ Technical Data	Safety Shutters Terminal Dimensions: 6.0mm x 6.5mm = 39mm² Conduit entries: Standard mounting block (40mm deep): 5 x 25mm entries Slim mounting block (25mm deep): 1 x 25mm rear entry 1 x Plain Reducer 25/20mm included in standard version
Installation	All entries should be silicone sealed to maintain IP rating Pips must be fitted to maintain IP rating Install vertically with sockets facing down Cover screws: tighten to 0.8Nm recommended
Compliance	AS/NZS3112: 2017 + A1 AS/NZS3100: 2022 + A1
Warranty	25 Years

DIMENSIONS

